

The X-1000+ is one of the most economical thermal transfer printers in its class. With a rugged all-metal construction and fast 4 inches per second printing speed, the X-1000+ provides efficiency and high reliability for medium-volume printing needs.

It has an 8-inches diameter label roll and 1182-foot length ribbon capacity for industrial standard throughput. The X-1000+ is supports all major barcode symbology including 2-D barcodes (PDF-417, Datamatrix and MaxiCode). Built-in 512K ROM and 512K RAM (upgradable to 1 MB) enable users to print long label formats (up to 45 inches).

The X-1000+ is supplied with free Windows software and Win95/98/2000/NT drivers for instant Plug and Play on delivery. It also supports popular programming languages for easy connectivity in different environments.

Optional accessories, including heavy duty cutters, peel-off kits, RAM and Flash memory cards, and stand-alone KDUs provide flexibility in the setup.



## Specifications

Printing method	Direct thermal & Thermal transfer	
Printing resolution	203 dpi (8 dots/mm)	
Max printing speed	2~4 ips (51~104 mm/s)	
Max printing length	0.5"~45" (13~1143 mm)	
Max printing width	1.0"~4.09" (25~104mm)	
Fonts	Int'l character sets standard from .049"~.23"H (1.25mm~6.0mm) 4 direction 0°~270° rotation	5 alpha-numeric fonts All fonts are expandable up to 24 x 24 Soft fonts are downloadable
Barcodes	Code 39, Extended Code 39 Code 128(Subset A,B,C) Codabar EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25	Code 93, Code 128 UCC Interleave 2 of 5, EAN-8 2&5 add on,
2D Barcodes	Maxicode, PDF-417	
Graphic	PCX bit map, GDI graphics	
Memory	512KB DRAM, 512KB Flash ROM	
Interfaces	RS-232 serial, Centronics parallel	
Media	Roll-feed, die-cut, continuous, fan-fold, tags, Ticket in plain paper or thermal paper Min width 1.0" (25 mm) Min length 0.4" (10 mm) Max roll capacity 8" (203mm) OD	Max width 4.3" (110 mm) Max length 0.4" (10 mm) Thickness .0025"~.01(.0635mm~.254mm) Core size 1.5"~3.0" (38mm~76mm) ID
Ribbon	Wax, Wax/Resin, Resin Ribbon roll-Max OD 3" (76mm) Ribbon width 1.3", 2.5", 3.3, 4.3" (33mm, 64mm, 84mm, 109mm)	Ribbon length- Max 1182" (360m) Code size- ID 1" core (25mm)
Compact size	W 9.8" x L 16.0" x H 10.2" (W 250x L 410 x H 260 mm)	
Weight	24.6 lbs (11 kgs)	
Power source	110/220 VAC ± 10%, 50/60 Hz	
Agency listing	CE, UL, CUL, FCC class A	
Operation environment	40°F ~ 100°F (4°C~38°C)	10~90% non condensing
Software	ARGOX PPLA & PPLB Language Label editing software – ArgoBar	Windows Driver (Win 31/95/98/NT) CODESOFT 4 XLT PLUS
Optional items	Cutter, Dispenser kit, Real time clock External 8"OD media stacker, ArgoNet print server	Extension SRAM memory, Extension flash memory, Standalone KDU - ArgoKee,