



## Z4 M™

Thermal, On-demand, Metal Bar Code Printer

### Get acquainted with a rugged, new Z Series™ metal printer—the Z4M.

The Z4M thermal printer has a personality all of its own - along with a rugged look and feel characteristic of a Zebra workhorse. Charcoal grey accents enhance the printer's sleek, contoured design while providing improved dirt-and smudge-resistance in the most industrial work environments.

### Powerful, price-performance leader

Get more value for money! One of Zebra's fastest printers at 254 mm (10") per second, this state-of-the-art metal printer with back-lit LCD control panel works hard, but is easy on your budget.



## Z4 M™

### Rugged construction

- Heavy-gauge steel media and electronics covers
- Die-cast aluminum base, frame and print-head mechanism

### Competitively priced, State-of-the-art printer

- Price-performance leader
- More standard features than any other printer in its class
- Print speeds up to (10") 254mm per second
- NEW ZebraLink connectivity and control solution

### Simple, reliable operation

- Standard back-lit LCD control panel for printer adjustments on the fly
- Print-head with "head open lock" stays in "full open" position for convenient media loading
- Full-size media window for easier viewing of your label and ribbon supplies
- Colour-coded operator cues, auto-calibration for intuitive operation and quick printer set-up



### Zebra Bar Code Products

*European Headquarters*  
Zebra House, The Valley Centre  
Gordon Road, High Wycombe  
Buckinghamshire, HP13 6EQ, UK  
Telephone: +44 (0) 1494 472872  
Fax: +44 (0) 1494 450103

*Regional Sales Office*  
Birkenwaldstr. 38  
D-63179 Obertshausen  
Deutschland  
Telephone: +49 (0) 6104 70990  
Fax: +49 (0) 6104 709922

*Regional Sales Office*  
50, rue Marcel Dassault  
F-92100 Boulogne-Billancourt  
France  
Telephone: +33 (0) 1 55 20 93 93  
Fax: +33 (0) 1 55 20 93 99

*International Headquarters*  
333 Corporate Woods Parkway  
Vernon Hills, IL 60061-3109 U.S.A.  
Telephone: +1 (847) 634-6700 or (800) 423-0422  
Fax: +1 (847) 913-8766

### Other Locations

*United States:* California, Florida, Rhode Island, Wisconsin

*Europe:* Italy

*Asia:* Hong Kong, Japan, Korea, Singapore

[www.zebra.com](http://www.zebra.com)



Reliability on demand™



## Standard Features

- Print methods: Thermal transfer or direct thermal
- Construction: Die-cast aluminium base, frame and print-head mechanism
- ZebraLink
- Metal media cover with large clear window
- Zebra E™ Print-head Energy Control
- Auto-calibration
- Auto-detectable power supply
- Colour-coded operator cues
- Back-lit LCD control panel

## Operating Characteristics

### Environment

- Operating Temp. 40°F/5°C to 105°F/40°C
- Storage/Environment -40°F/-40°C to 140°F/60°C
- Operating Humidity 20-85% non-condensing
- Storage Humidity 5-85% non-condensing

### Electrical

- Universal auto-detectable (PFC-compliant) power supply 90-265 VAC; 48-62 Hz; 5A fused

## Media Characteristics

### Labels

- Max. Roll Size
- 8"/203mm O.D. on a 3"/76mm I.D. core
- Thickness (label & liner)
- .0023"/.058mm to .01"/.25mm

### Media Types

- Continuous or fanfold, die-cut, notched, tag stock, black mark, perforated

For optimum print quality and printer performance, use genuine Zebra supplies.

## Fonts/Graphics/Symbologies

### Fonts and Character Sets

- Standard Fonts: 9 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
- Sets: IBM® Code Page 850 International character set
- Optional European and Asian font sets

### Graphic Features

- Supports user-defined fonts and graphics – including custom logos
- ZPL II drawing commands – including boxes and lines

## Options and Accessories

- 300dpi printhead
- Up to 2MB Flash; up to 8MB via PCMCIA card
- Cutter with catch tray
- Value peel – a front mount, passive peel option with no liner take-up
- Liner take-up (works with value peel option) – full roll liner take-up spindle (comes without rewind; fits standard printer base)

## Zebra Programming Language

- ZPL™ & ZPL II® – universal language for Zebra printers. Simplifies label formatting and enables seamless compatibility with other Zebra printers.
- ZBI – works with ZPL to control and interpret text and data streams from peripherals and non-ZPL printer programming languages. Transmits captured data over LAN, WAN or wireless network via e-mail or TCP/IP messaging.

## Communication Interface Capabilities

- RS-232C/422/485 serial port
- Bi-directional parallel port

## Agency Approvals

- UL 1950; CISPR 22 (Class B); IEC 950; 801-2, -3 and -4 standards; Canadian Doc. (Class A); FCC (Class B); CE compliance

## Ribbons

Ribbon is recommended to be at least as wide as media.

### Max. Roll Size

- 3.2"/81.3mm O.D. on a 1"/25.4mm I.D. core

### Standard Lengths

- 1476"/450m; provides 2:1 & 3:1 media roll to ribbon ratios

### Ribbon Set-up

- Ribbon wound ink side out

## Bar Code Symbologies

- Linear Bar Codes: Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digital extensions, Plessey, POSTNET, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar
- Two-Dimensional: CODABLOCK, PDF-417, Code 49, DataMatrix, Maxi Code, QR Code, Micro PDF-417
- Rewind – internally rewinds full label roll on 76.2mm (3") core (comes with 101.6mm (4"), non-standard printer base)
- PCMCIA connector (supports PC cards up to 8MB)
- ZebraNet® PrintServer II (for Ethernet connectivity)
- BAR-ONE® software
- European and Asian font sets



## Z 4 M



## ZebraLink™

ZebraLink, a revolutionary real-time connectivity and control solution for Zebra printers, includes:

1. **WebView** – enables the remote monitoring and configuration capability of Zebra printers in real-time using Web-based tools.
2. **Alert** – enables a Zebra printer to receive or send error Alert condition messages via the Internet.
3. **ZBI™** – programming language that works with ZPL II to control and interpret incoming text and data.

ZebraLink gives you the freedom to replace other bar code printers with the superior performance and reliability of Zebra printers, without costly reprogramming of your host system. Or, you can create a stand-alone application using the Z4M printer and, for example, a scanner or weighing-scale, without the need for a PC. Internet-aware, ZBI can transmit data captured by these peripheral devices over your LAN, WAN or wireless network via e-mail or TCP/IP messaging.

The rugged Z4M is ideal for a wide variety of applications, including:

- Shipping/receiving
- Compliance labelling
- Asset tracking
- Inventory control
- Ticketing
- Work-in-process
- Commercial/small business

## Maximum Print Area

Width: 4.09"/104mm

Length with 203dpi:

105"/2,667mm (with standard memory)

Length with 300dpi:

49"/1,245mm (with standard memory)

## Resolutions

203dpi/8dots per mm; 300dpi/12dots per mm

## Maximum Print Speed

10"/254mm per second (with 203dpi)

## Memory

Standard: 4MB DRAM (2MB user available)

Optional: Up to 2MB Flash; up to 8MB Flash via PCMCIA card

## Physical Characteristics

Width: 10.93"/278mm

Depth: 18.69"/475mm

Height: 13.32"/338mm

Weight: 32.4lbs/15kg

## Media Specifications

Label and liner width:

1"/25.4mm to 4.5"/114mm

Ribbon width:

2"/51mm to 4.33"/110mm

\*Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved.